

AT-65/AT-60

ANALOG DESKTOP PHONE



AT-65 DESKTOP PHONE

- > Support Message Waiting Lamp
- > Handset volume control [SW]
- > Ringer volume control [HW]
- > 3 one-touch buttons
- > Wall mountable



AT-60 SIMPLE DESKTOP PHONE

- > Support Message Waiting Lamp
- > Handset volume control [SW]
- > 3 one-touch buttons
- > Wall mountable



AT-65 / AT-60		
Model	AT-65 AT-65P(BK)TEL / AT-65P(WH)TEL AT-65M(BK)TEL / AT-65M(WH)TEL	AT-60 AT-60P(BK)TEL / AT-60P(WH)TEL AT-60M(BK)TEL / AT-60M(WH)TEL
Display	No	No
PSTN	No (Use for Behind PBX)	No (Use for Behind PBX)
Dialing Method	DTMF / DP 10pps/ DP 20pps*	DTMF
Message Waiting Lamp	Yes	Yes
One Touch Key	3 buttons	3 buttons
Speakerphone	No	No
Redial Key	Yes	No
Flash Key	Yes	No
Speaker Key	No	No
Hold Key	No	No
Hook Switch	Mechanical	Electromagnetic
Receiver Volume	Yes	Yes
Battery	Not Required	Not Required
Wall Mount	Yes	Yes
Branch Connect	No	No
Music on Hold	By PBX	N/A
Dimension	207(W) x 204(D) x 78(H) mm	66(W) x 159(D) x 158(H) mm
Weight	0.6 kg	0.5 kg
Communications Platform	SV9500, SV9300, SV9100, SL2100	

*AT-65M(BK)TEL and AT-65M(WH)TEL support DTMF only

NEC and the NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All trademarks identified with © or TM are registered trademarks or trademarks of their respective owners. Models may vary for each country, and due to continuous improvements this specification is subject to change without notice. Please refer to your local NEC representative(s) for further details.

Corporate Headquarters(Japan)
NEC Corporation
www.nec.com/univerge

For further information please contact NEC Corporation or: